

Pocket-sized Mobile Computer



Only 210 g!



IEEE
802.15



IEEE
802.11 b/g



FEATURES

- High Performance Laser Reader
- Ergonomic, compact and robust
- Microsoft Windows CE 5.0
- Intel PXA Microprocessor
- Wireless communication option (IEEE 802.15 Bluetooth®, IEEE 802.11 b/g)
- Sharp and bright color TFT QVGA display with touch screen
- User-accessible SD memory slot
- Lightweight 7.4 oz (210 g)
- 4 ft (1.2 m) drop resistance
- IP54 protection class

APPLICATIONS

- Inventory
- Shelf replenishment
- Price management
- Order entry
- Assisted sales
- Line busting

HIGHLIGHTS

• COMPACT

The Datalogic Memor™ is small and slim, with excellent ergonomics for single-handed use.

• INNOVATIVE

The Datalogic Memor™ is a real innovation on the market thanks to:

- an industrial standard OS for simpler application development and porting
- a mature and stable architecture
- a large memory on board to store applications and data
- a user accessible SD card slot to backup data or manage a large DB
- an integrated WLAN or WPAN to allow immediate access to any infrastructure

...all in an extremely compact package!!!

• ROBUST

The Datalogic Memor™ is provided with rugged construction to survive unintentional drops and exposure to water and dust.

• VERSATILE

The color TFT QVGA display with touch screen and phone-like numeric keypad satisfy all mobile application needs.

• READY-TO-USE

The Datalogic Memor™ is supplied with a power supply and mini USB cable.

A full set of software tools are readily available on-board:

- Terminal Emulation (TCL™)
- DL Application Manager™
- Locked Web Browser™

Specifications

PHYSICAL CHARACTERISTICS

DIMENSIONS	152 x 55 x 40 mm (5.98 x 2.17 x 1.57 in) (maximum)
WEIGHT	210 g (7.41 oz) incl. standard battery
DISPLAY	Reflective TFT daylight readable color display, 240 x 320 pixels, 56 mm (2.2 in) diagonal, 64 K colors, backlight, touch screen
KEYBOARD	20 rubber keys, 5-position joystick, backlit keyboard standard
OPERATING TEMPERATURE	0 ° +50 °C (32 ° to 122 °F)
STORAGE TEMPERATURE	-10 ° +65 °C (14 ° to 149 °F)
DROP RESISTANCE	Withstands drops from 1.2 m (3.94 ft) onto concrete
ENVIRONMENTAL SEALING	IP54 standard for water and dust resistance

SYSTEM

OPERATING SYSTEM	Microsoft Windows CE 5.0
MICROPROCESSOR	Intel® XScale PXA255 @ 200 MHz
SYSTEM RAM MEMORY	64 MB
SYSTEM FLASH MEMORY	128 MB (including Backup directory for user data & programs permanent storage)
EXPANSION SLOTS	Secure Digital (user accessible)
REAL-TIME CLOCK	Time and date stamping under software control
POWER SUPPLY	Removable battery pack with rechargeable lithium polymer batteries; 3.6 V 1000/2000 mAh (3.6/7.2 Watt hours); alkaline batteries compatible Local connection (customized and mini USB connector) for fast battery charging

COMMUNICATIONS

INTERFACES	Electrical: integrated RS232 up to 115.2 Kbps USB: integrated high speed USB and mini USB connector (USB 1.1)
LOCAL AREA NETWORK (LAN)	IEEE 802.11b/g (optional) Integrated module
PERSONAL AREA NETWORK (PAN)	Frequency range: Country dependent, typically 2.4 - 2.5 GHz IEEE 802.15 Bluetooth® (optional) Integrated module

READING OPTIONS

LASER CHARACTERISTICS	
SCANNING RATE	104 ± 12 scan/sec
MINIMUM RESOLUTION	0.10 mm / 4 mils
DEPTH OF FIELD	5 to 90 cm (2 to 35 in), depending on bar code density
BAR CODES	EAN/UPC, Code 39, 2/5 Codes, Plessey, Codabar, Code 128, EAN128, MSI, Code 93, Code 11
LASER CLASSIFICATION	VLD - Class II EN 60825-1/CDHR

SOFTWARE

DEVELOPMENT	CONFIGURATION & MAINTENANCE
Windows CE SDK™	Wavelink® Avalanche™
DL Mobility Developer Assistant™	DL Application Manager™
MCL-Collection™	DL Mobile Director Enterprise™
Java Virtual Machine (Crème)	
TERMINAL EMULATION	UTILITIES
DL-TCL™	Locked Web Browser™
	DL Keep Connecting™

Accessories



Single Cradle



Inside the box



Software

For more information and software downloads see: www.mobile.datalogic.com/memor

Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.

Printed in the Italy, June 2007



9C0005558