

Product Profile

- The MicroBar 9730's input device ports are compatible with all Intermec wand, CCD and laser scanners, magnetic stripe readers, slot readers and any RS232C device.
- The 9730 can connect most non-Intermec input devices on the market today.
- Connects to over 1500 interfaces including PC's (IBM®/Compatibles - many keyboard types), Apple®, and a range of terminals including IBM® 3XXX, HP, and Wyse.
- Fast decoding UPC, EAN, ISBT-128, Code 39, Code 128...up to 20 different symbologies can be auto-discriminated and rapidly decoded by the 9730.
- 9730's Data Formatter can be used to format bar codes according to type of symbology, bar code length, data structure, and input port.
- The 9730 offers a variety of commands that can perform various functions, such as searching, deleting, filling, and truncating.
- The 9730 uses the EasySet set-up software for quick and easy installation.
- Flash EPROM is included for ease of future upgrades and as an application platform.



MicroBar 9730 DECODER

The MicroBar 9730 is a compact universal external decoder and interface adapter that connects Automatic Data Capture (ADC) devices to the widest range of PC's and terminals. The 9730 can be used to decode the output of a simple bar code wand or as a platform for advanced applications. Easy to install, the 9730 can connect multiple ADC inputs (wands, hand-held scanners, magnetic stripe readers, and RS232 devices, and many more) to PC's or terminals via their keyboard or RS-232 ports.

The MicroBar 9730 is suitable for connecting bar code wands and scanners to PC's in home, office, health, libraries, post office and industrial applications, and for connecting multiple input devices to a single terminal in retail.

For advanced users the 9730 is an application platform that provides extremely powerful data formatting capabilities. 20 full ASCII characters can be specified as a pre/postamble. An additional 15 address characters can be added per port. Masking and re-ordering can be performed on up to 120 characters. With 5

masks selectable by symbology, port, length, characters, and 100 characters—all data formatting types. This allows the full power of a bar code system to be applied to specific applications.

Despite its powerful capabilities the 9730 is easy to install. Using EasySet set-up software, with its simple Windows™ interface, the 9730 is quickly and easily configured for use. All key parameters of bar code symbologies, data format and transmission are made by simple EasySet commands, cloning or bar code menus. EasySet has a unique concatenation feature that allows a complete set up to be printed as one set-up bar code. A single unit connects via keyboard or serial RS-232 ports without modification. This simplifies stocking, reduces delivery time and provides flexibility for future updates of PC's and terminals. The 9730 features a good read LED and buzzer for the operator. In keyboard emulation mode (wedge) the input data appears as if it were keyed in, enabling immediate compatibility with the host's hardware and software. No software tools are required.

General Description

- Universal solution for connecting data capture devices
- Suitable for applications in retail, office, healthcare, libraries and industrial applications
- Includes extensive data formatting commands
- Connects up to 4 input devices including Laser, Wand and RS232 devices
- Wedge, RS232 and dual RS232 (serial) interfaces

Physical Characteristics**Height:** 35mm (1.38")**Length:** 85 mm (3.35")**Width:** 84mm (3.3")**Case:** High impact ABS self-extinguishing plastic**Inputs**

Up to 4 inputs via 9 pin D sub, RJ 6 and RJ 10 Pin connectors for hand-held bar code scanners (wand, CCD or laser), fixed bar code scanners, Magstripe readers (decoded or undecoded), badge readers, and serial RS232 TTL/C devices (smart-card, OCR readers, scales, etc.)

Outputs

Wedge to PC keyboards, including IBM PC's/compatibles, Apple Mac®, and many retail terminals (including IBM® 3XXX, NCR, Wyse, etc.)

Decoder Performance

UPC E, A, EAN, Code 39; Interleaved, Matrix, Industrial and Standard 2 of 5; Code 128, UCC EAN 128, Codabar, Code 11, Code 93, Ames, MSI, Plessey, Telepen, ISBT-128

Data Formatting**Pre- and postambles:** 20 characters + 2 characters for AIM symbology identifiers**Port address:** 15 characters**Masking and re-ordering:** Masking by symbology, port address, length of string and presence of specific characters**Environment****Operating temperature:** -20° to 55°C (-4° to 131°F)**Storage temperature:** -25° to 70°C (-13° to 158°F)**Relative humidity:** Non-condensing (5% to 95%)**MTBF:** 50,000 hours**Shock:** Withstands multiple drops of 1.5m (5 ft) to commercial flooring**Electrostatic discharge:** 8kV to any external surface**Electrical Characteristics****Power requirements:**

+5VDC ±5% or +5-12VDC ±5%

Current consumption: 35 mA no external load**Advanced Features**

User programmability of data format, variable time-out, code identification, preambles and postambles, intercharacter and intermessage delays, and many others

Set Up

Bar code menus, cloning, or EasySet software

Regulatory Approvals

EN 55022/CISPR 22 Class B

FCC Part 15 & ICES-003 Class B

AS 3548, C tick Marked

Compliant with all European Directives, CE Marked

Other approvals pending

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
tel: 425.348.2600
fax: 425.355.9551

Systems & Solutions

550 2nd Street S.E.
Cedar Rapids, Iowa 52401
tel: 319.369.3100
fax: 319.369.3453

Media Supplies

9290 Le Saint Drive
Fairfield, Ohio 45014
tel: 513.874.5882
fax: 513.874.8487

**Europe/
Middle East & Africa**

Headquarters
Sovereign House
Vastern Road
Reading, Berkshire RG1 8BT
United Kingdom
tel: +44.118.987.9400
fax: +44.118.987.9401

Gothenburg

Idrottsvägen 10
P.O. Box 123
SE-431 22 Mölndal
Sweden
tel: +46.31.869500
fax: +46.31.869595

**Asia/
Latin America**

Hong Kong
26-12 Shell Tower
Times Square
1 Matheson Street
Causeway Bay
Hong Kong
tel: 852.2574.9777
fax: 852.2574.9725

Singapore

25-16 International Plaza
10 Anson Road, 079903
tel: 65.324.8391
fax: 65.324.8393

Australia

Level 7, 200 Pacific Highway
Crows Nest NSW 2065
Australia
tel: 61.2.9901.2065
fax: 61.2.9954.6300

South America and Mexico

17921 B Skypark Circle
Irvine, California 92614
tel: 949.442.9393
fax: 949.757.1687

**Worldwide
Fax Document
Retrieval Service**

800.755.5505
(North America Only)
tel: 650.556.8447

Internet

www.intermec.com

Sales

800.347.2636
(toll free in N.A.)
tel: 425.348.2726

Service and Support

800.755.5505
(toll free in N.A.)
tel: 425.356.1799

Copyright © 2002 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 608530-01B 01/02

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.