



# SYMBOL AP 7502 802.11ac ACCESS POINT

## ENTERPRISE CLASS WALL PLATE 802.11AC ACCESS POINT

### EASILY DELIVER COST-EFFECTIVE HIGH-PERFORMANCE WIRELESS CONNECTIVITY IN PUBLIC-FACING MICRO-CELL ENVIRONMENTS

Whether you are responsible for a hotel, assisted living facility, dormitory housing or an apartment complex, you are challenged with providing high-speed Internet access in a challenging environment with many rooms rooms with RF-blocking walls, floors and doors. You need a cost-effective way to provide the dependable desktop style wireless speeds your users expect in-room on however many consumer mobile devices they may own including 2.4 GHz and the newer 5 GHz smartphones and tablets. To further complicate the challenge, todays users are watching videos, making video calls and posting on multi-media heavy social networking websites on their mobile devices all bandwidth-heavy applications that require a latency- and jitter-free connection.

Introducing the easiest way to solve these big business problems the AP 7502, the pocket-sized 802.11ac access point. The AP 7502 is purpose built for public-facing micro-cell environments such as hotel and patient rooms, classrooms and apartments. The dual 802.11n and 802.11ac radios, five internal antennas, plus a host of Zebra-only features provide a dependable high-performance wireless connection for every user and every mobile device in the room. Its revolutionary small size makes it easy to install anywhere, while the understated design allows it to easily hide in plain sight. Deployment couldnt be easier or faster the AP 7502 can be installed in just a few minutes, with zero-touch automatic configuration. And locationing support, including Bluetooth® SMART, opens the door to a world of applications that can help provide users with a world-class experience that will put your organization a step above the competition.

### TWO RADIOS FOR COMPREHENSIVE MOBILE DEVICE SUPPORT

With its dual 802.11n and 802.11ac radios, the AP 7502 supports all the mobile devices that walk through your door, from legacy 2.4 GHz devices to todays new 5 GHz consumer smartphones. The next generation 802.11ac radio empowers your network with fifth generation Wi-Fi more than double the throughput of 802.11n helping provide the capacity and speeds your network needs to handle multiple devices running multiple bandwidth-hungry applications.

### SUPERIOR WI-FI PERFORMANCE

This little access point is equipped with big business features that provide your users with the seamless enterprise-class wireless services they expect. Two features that are optimized for micro-cell environments work hand-in-hand to eliminate RF interference and the resulting degradation of the quality of the wireless connection that can occur. Adaptive RF Power automatically detects nearby access points and adjusts output power as needed, while Automatic Channel Selection ensures the selection of an unused or least used channel. And three features prevent too many users or traffic overload from reducing the quality of service on a specific AP 7502. Load balancing monitors the number of users on any specific access point and when needed, works with RoamAssist to override any client stickiness, ensuring clients can roam to an access point that will provide a better signal. Pre-emptive roaming can work hand-in-hand with Roam Assist to provide a mobile-phone-style fast and seamless roaming experience.

### **INSTALL IN JUST A FEW MINUTES**

Installation is literally a snap just mount the bracket wherever you like and snap the AP 7502 into the bracket. If desired, a decorative trim plate can be snapped on over the AP 7502 to add a more polished look for devices that are installed in visible areas. With 802.3af/at PoE support, the need to run expensive cabling to provide power to the AP 7502 is eliminated. And with true zero-touch provisioning, the AP 7502 is automatically discovered and configured no hands on required.

### **TAMPER-PROOF DESIGN**

Since the AP 7502 is readily accessible to guests and patients, we made it virtually tamper-proof. Once the AP 7502 is snapped into its metal bracket that is mounted to the wall, it cannot be removed without a special tool. For additional security, you can also bolt the AP 7502 directly to the metal bracket with a special torque screw that also cannot be removed without a special tool. And to make the tiny AP 7502 even harder to spot, You can also turn off the status LED lights via the central controller.

### **ROBUST LOCATIONING SERVICES**

With integrated support for Bluetooth SMART, Wi-Fi locationing and Apples iBeacon, you can connect to user mobile devices when they are in the room to extend special discounts and other valuable information, strengthening the customer relationship and providing a true competitive advantage. In addition, you can automatically track nearby assets that are enabled with locationing tags, allowing you to spend less time managing assets, yet have better visibility into asset location and status.

### **COST-EFFECTIVELY POWER SECURITY CAMERAS AND MORE WITH POE PASSTHROUGH**

Not only does the AP 7502 provide wireless connectivity, it can also power a wide variety of equipment. With 802.3af compatible PoE out, you can easily provide power to an IP security camera, a Voice-over-IP phone, another access point, a dedicated environmental sensor and more, all without the expense of running power cables.

### **EASY AND FLEXIBLE MANAGEMENT MODES**

Choose the management mode that best meets the needs of your technology environment. The AP 7502 can be easily managed and adopted by a Zebra wireless controller. With virtual controller mode, one AP 7502 can adopt up to 24 additional AP 7502 access points by simply logging into one AP 7502 and clicking on a single checkbox ideal for smaller organizations that dont require or want a wireless switch. In addition, the AP 7502 can also operate in standalone mode, where it can be managed individually, ensuring the continuation of wireless services even if the connection to the centralized controller is lost.

### **SUPPORT SERVICES BRING OUR EXPERTISE RIGHT TO YOUR DOOR**

A respected leader in enterprise mobility, Zebra provides services that allow you to benefit from the experience weve gained from working around the globe with many of the worlds leading companies in practically every vertical market. Our family of services can help you get and keep your WLAN up and running at peak performance by providing the assistance you need at every phase of network lifecycle from planning and implementation to post-deployment everyday support. Not only can we help you tailor your network to meet your specific needs, we can also help you reduce risk, lower your capital investment and reduce operational costs.

**The AP 7502 micro-cell access point providing low-cost high-performance Wi-Fi services in guest rooms, patient rooms, classrooms and more.**

For more information, please visit [www.zebra.com/wlan](http://www.zebra.com/wlan) or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact) us

# TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS		AVAILABLE INTERFACES	
<b>Dimensions</b>	3.5 in. L x 3.7 in. W x 1.35 in. H 90 mm L x 95 mm W x 35 mm H Extends into wall cavity .25 in./7mm	<b>802.11 Wireless Interface</b>	Dual Radio; 802.11a/b/g/n/ac 2.4GHz and 5.2GHz
<b>Weight</b>	0.5 lbs./0.23 kg	<b>Bluetooth LE Interface</b>	Single BLE transceiver
<b>LED Activity Indicators</b>	Two single color status LEDs	<b>LAN Ethernet ports:</b>	3 x IEEE 802.3 10/100Mb auto-sensing
		<b>Uplink LAN Ethernet</b>	1 x IEEE 802.3 Gigabit Ethernet auto-sensing
NETWORKING SPECIFICATIONS		RADIO SPECIFICATIONS	
<b>BSS</b>	8 BSSIDs; 16 SSIDs	<b>Wireless medium</b>	Direct Sequence Spread Spectrum (DSSS), Orthogonal Frequency Division Multiplexing (OFDM), Modulation and Coding Scheme, (MCS), High Throughput (HT )
<b>Layer 2 and Layer 3</b>	802.1Q, 802.1D, DHCP Server/client, BootP, PPPoE, LLDP, GRE and IPSec	<b>Network standards</b>	IEEE 802.11a/b/g/n/ac, 802.11d and 802.11i WPA2 and WMM
<b>Security</b>	Stateful L2/L3 firewall, IP filtering, NAT, 802.1x, 802.11i, WPA2, Dedicated fulltime WIPS sensor mode, secure guest access captive portal	<b>Data rates supported</b>	802.11b: 1, 2, 5.5 and 11 802.11g/a: 6, 9, 12, 18, 24, 36, 48 and 54 Mbps 802.11n: MCS 0-15 up to 300 Mbps 802.11ac: MCS 0-8 up to 867 Mbps
<b>Management</b>	SSH, HTTPS, SNMPv3	<b>Operating frequencies</b>	2412 to 2472MHz, 5180 to 5850 MHz Actual channels depend on country limitations
<b>Quality of Service (QoS)</b>	WMM, 802.1P, DSCP. Applied per radio, WLAN and user	<b>Antenna configuration</b>	2.4Ghz: Two internal omni-directional, 1x2, 2x2, MIMO, 3dBi peak gain 5Ghz: Two internal omni-directional, 1x2, 2x2, MIMO, 5dBi peak gain Bluetooth: one internal omni-directional
POWER		<b>Transmit power</b>	6dBm to 15dBm per transmit chain 1dB increments (Actual transmit power dependent on national limits. )
<b>Access point</b>	6.5w operating	<b>Receiver sensitivity</b>	2.4GHz band: -96dBm @ 1Mbps; -74dBm @ MCS7 40mHz 5.2GHz band: -95dBm @
<b>PoE PD</b>	802.3af, 802.3at		
<b>PoE PSE</b>	802.3af when input is 802.3at; ~6.5w when input is 802.3af; no output when input is DC wall brick		
MOUNTING			
Universal mounting bracket for worldwide structured cable boxes; includes US 70 mm x 115 mm decor trimplate			
ORDERING INFORMATION			
<b>AP-7502-67030-US</b>	802.11ac/802.11n Dual Radio Wallplate AP;		
<b>AP-7502-67030-WR</b>	Universal mounting bracket and US sized decorative trim included		
<b>AP-7502-67030-EU</b>			

AP-7502-67030-  
APME

6Mbps; -73dBm @ MCS7  
40MHz

AP-7502E-67030-  
US  
AP-7502E-67030-  
WR  
AP-7502E-67030-  
EU

802.11ac/802.11n Dual  
Radio Wallplate AP; USsized  
decorative trim included

Bluetooth LE

2400 - 2483.5KHz in 2MHz  
channels, user configurable  
UUID, beacon period, format

---

#### ENVIRONMENTAL

---

32 ° F to 104° F/0 ° C to 40° C, 5% to 90%  
non-condensing

---

#### REGULATORY

---

FCC 15.247, 15.407 / EN300 328, EN 301 893; UL  
EU EN 60950-1 2nd Ed., ANZ RCM, UL 2043;  
FCC Part 15 Subpart B, EN 55022: 2010 + A1:  
2007, ICES 003 (Class B) EN 55024: 2010 + A1:  
2001 + A2: 2003; EU RoHS Directive 2011/65/EU  
(EN50581: 2012 Standard); CE, IC, FCC

ZEBRA WLAN  
UNLEASH OPTIMAL



**ZEBRA**



Part number: SS-AP7502-A4. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. SYMBOL is a trademark owned by Symbol Technologies, Inc., which is an indirect wholly owned subsidiary of Zebra Technologies Corporation. All rights reserved. All other trademarks are the property of their respective owners.

---

**ZEBRA TECHNOLOGIES**